

Category		Type	1F	1H	1E	1J	2A	2B	2E	2H(W2H)	3A(W3A)
		Size inch (mm)	01005 (0.4×0.2)	0201 (0.6×0.3)	0402 (1.0×0.5)	0603 (1.6×0.8)	0805 (2.0×1.25)	1206 (3.2×1.6)	1210 (3.2×2.5)	2010 (5.0×2.5)	2512 (6.4×3.2)
Thin Film Resistors	Precision	RN73H/RN73R			- / -	■ / ■	■ / ■	■ / ■	■ / ■		
	Resistance Tolerance: ±0.05~, T.C.R.: ±5×10 <sup>-6</sup> /K~										
Thick Film Resistors	Precision	RS73			- (RT)	■ (RT)	■ (RT)	■ (RT)			
		Resistance Tolerance: ±0.1~, T.C.R.: ±25×10 <sup>-6</sup> /K~									
	Anti Surge Anti Pulse	RK73G		■ (RT/AT)	■ (RT/AT)	■ (RT/AT)	■ (RT/AT)	■ (RT/AT)	■ (RT/AT)		
		Resistance Tolerance: ±0.25~, T.C.R.: ±50×10 <sup>-6</sup> /K									
	High Temperature	SG73/S/P		■ (RT)	■ (RT/AT)	■ (RT/AT)	■ (RT/AT)	■ (RT/AT)	■ (RT)	■ (RT)	■ (RT)
		Power Rating: 0.1W~1W(SG73P, 1E:0.25W, 1J:0.33W, 2A:0.5W, 2B:0.75W, 2E:1W), SG73S: For Surge, SG73P: For Pulse									
	Wide Terminal	SG73G			■ (AT)	■ (AT)	■ (AT)				
		Resistance Tolerance: ±0.25~, T.C.R.: ±50×10 <sup>-6</sup> /K, For Pulse									
	High Voltage	HSG73P			- (RT/AT)	■ (RT/AT)	■ (RT/AT)	■ (RT/AT)	■ (RT/AT)		
		Power Rating, 1E:0.2W, 1J:0.33W, 2A:0.5W, 2B:0.75W, Operating Temp., Sn Terminal: ~175°C, Au Terminal: ~200°C									
	General	WK73			-	-	■ (RT)	■ (RT)		■ (RT)	■ (RT)
		Resistance Range, WK73R: 10Ω~1MΩ, WK73S: 10mΩ~9.76Ω, Power Rating: 0.33W~3W									
Jumper	WG73						■		■ (RT)	■ (RT)	
	Resistance Range: 560mΩ~1kΩ, Power Rating, 2B: 1W, 2H: 1.5W, 3A: 2W, For Pulse										
Current Fuses	HV73/HV73V				■ / ■ (RT) (RT/AT)	■ / ■ (RT) (RT/AT)	■ / ■ (RT) (RT/AT)	■ / ■ (RT) (RT/AT)	■ / ■ (RT) (RT/AT)	■ / ■ (RT) (RT/AT)	■ / ■ (RT) (RT/AT)
	Resistance Range: 10kΩ~100MΩ, Max. Working Voltage, 1J: 350V, 2A: 400V, 2B: 500V, 2H: 2,000V (D.C.), 3A: 3,000V (D.C.)										
Protectors	Current Fuses	RK73H/RK73B	■ / ■ (RT) (RT)	■ / ■ (RT) (RT)	■ / ■ (RT/AT) (RT/AT)	■ / ■ (RT/AT) (RT/AT)	■ / ■ (RT/AT) (RT/AT)	■ / ■ (RT/AT) (RT/AT)	■ / ■ (RT/RT) (RT/RT)	■ / ■ (RT/RT) (RT/RT)	■ / ■ (RT/RT) (RT/RT)
		Resistance Tolerance, RK73H: ±0.5%, ±1%, RK73B: ±2%, ±5%									
Current Fuses	Current Fuses	RK73Z	■ (RT)	■ (RT/AT)	■ (RT/AT)	■ (RT/AT)	■ (RT/AT)	■ (RT/AT)	■ (RT)	■ (RT)	■ (RT)
		Resistance, 50mΩ Max. (1H(RT): 100mΩ Max.), Current Rating, 1F · 1H: 0.5A, 1E · 1J: 1A, 2A~W3A: 2A									
Current Fuses	Current Fuses	TF16VN				■					
		Rated Current: 0.40A~3.15A, Rated Voltage: DC32V~DC125V, For Automotive									

Not to exact size

RT: Anti sulfuration type are available AT: Heat shock resistance type are available

Category		Type		1F	1H	1E	1J	2A	2B	2E	2H(W2H)	3A(W3A)	
		Size	inch (mm)	01005 (0.4×0.2)	0201 (0.6×0.3)	0402 (1.0×0.5)	0603 (1.6×0.8)	0805 (2.0×1.25)	1206 (3.2×1.6)	1210 (3.2×2.5)	2010 (5.0×2.5)	2512 (6.4×3.2)	
Thick Film Resistors	Low Resistance	SR73			-	■ (RT)	■ (RT)	■ (RT)	■ (RT)	■ (RT)			
		Resistance Range: 24mΩ~10Ω, T.C.R.: ±100×10 <sup>-6</sup> /K~											
		UR73/D/V				/ = /	/ = /	■ / ■ / ■	■ / ■ / ■	■ / ■ / ■		/ 10L0 /	/ 10L0 /
Resistance Range: 10mΩ~100mΩ, T.C.R.: ±75×10 <sup>-6</sup> /K~													
		WU73							■				
Resistance Range: 10mΩ~100mΩ, T.C.R.: ±75×10 <sup>-6</sup> /K~, Wide Terminal													
Shunt Resistors (Metal Plate)	Current Sensing	TLR						■					
	Resistance Range: 0.5mΩ~20mΩ, Power Rating: 0.5W~5W, T.C.R.: ±50×10 <sup>-6</sup> /K~												
		TLRZ				-	-	-	-				
0.2mΩ Max.(1E: 0.5mΩ Max), 1E: 10A, 1J: 26A, 2A: 31.6A, 2B: 50A													

Category		Type	Size					
Leaded Resistors (Ceramic)	High Voltage	PCF		1/2W		1W		2W
		Resistance Range: 3.3Ω~390kΩ, Power Rating: 0.5W, 1W, 2W, Max.Pulse Voltage, 1/2W: 10kV, 1W: 14kV, 2W: 20kV						
	HPC		1/2W		3W		5W	
Resistance Range: 3.3Ω~390kΩ, Power Rating: 0.5W, 1W, 2W, 3W, 4W, 5W, Max.Pulse Voltage, 1/2W: 8kV, 1W: 15kV, 2W~5W: 25kV								
	Power Resistor	BGRV BWRV BSRV		3W		5W		20W
			S Style		N Style		Q Style	
Power Rating: 3W, 5W, 7W, 10W, 15W, 20W, 30W, 40W(60W), BGRV: Wirewound(Glass Core), BWRV: Wirewound(Ceramic Core), BSRV: Metal oxide film(Ceramic Core), For Automotive								