



## POWER DENSITY/DOWNSIZING PRODUCT OPTIONS

Watt	2512	2010	1210	1206	0805	0603	0402	0201	01005
0.03									RK73B/H1F*
0.05								RK73B/H1H*	
0.1						RK73B/H1J*	RK73B/H1E*	SR731H	
0.125						RK73B/H1J*	SG73P/S1E*		
0.2							SG73P/S1E*		
0.25				RK73B/H2B*	RK73B/H2A* SG73P/S2A*	SR731J*	SG73P1EW		
0.33				SG73P/S2B* SR732B*	SR732A*	SG73P/S1J* WN73H1J †	WK73R1E		
0.5			RK73B/H2E* SG73P/S2E* SR732E*		SG73P/S2A*	WK73R1J			
0.75		RK73B/H2H* SR732H*	SG73P/S2E*	WK73R/S2B* SG73P/S2B*	WK73R2A*				
1.0	RK73B/H3A* SR733A	WK73R/S2H*	SG73P/S2E1*	WG732B WN73H2B WU732B WK73R/S2B* UR73V (D/H) 2B**	WK73R/S2A*				
1.5	WK73R/S3A*	WG732H		WK73R/S2B15* WU732B15					
2.0	RK73B/HW3A2* WG733A WK73R/S3A*	WK73R/S2H2*							
3.0	WK73R/S3A3*								

= Rated Terminal Temp. below 125°C

Rated Terminal Temp. is above 125°C unless otherwise noted

\* Available in Anti-Sulfur Version \*\* Non-Sulfur Sensitive += 0.3 Watt